

P/N:MEF 335J250VAC P=22.5

Capacitance 容量	@ 1KHZ 23°C±3°C	Tolerance 误差	±5%	Rated Voltage 额定电压	@ 25°C 50/60HZ	DRAWING & MARKING	Protection/Coating 外封装	Flame retardant epoxy resin (UL94V-0)
	3.3 µF			Construction 结构	250VAC		Resin filled 灌封	
Dielectric 介质	Polyester film	Plates 导体	Metallized Aluminum	Construction 结构	Winding	DN	Lead Wire 导线	Φ 0.8 tinned steel copper wires
				1.00% 1.50%			Colour 颜色	red
Dissipation Factor 损失角	@ 1K HZ 1Vrms 25°C max		50~60KHZ 1KHZ 10KHZ 150KHZ	DC lead to lead DC lead to case AC lead to lead AC lead to case				
Test Voltage 测试电压	1.6 times of rated voltage for 5 seconds cut off current at 10mA			400VDCVDCVACVAC				
Dielectric Withstanding Voltage 介质耐压强度	Between terminals 250VACx 200% 1To 5 sec max			500VDC				
Insulation Resistance 绝缘阻抗	20°C@ 100 VDC 60 seconds min 20°C@.....VDC..... seconds min		Lead to lead Lead to case	>3000 MΩ*ufMΩ				
dv/dt 单位时间电压变化率	max		Max pulse rise time	(v/sec)				
IpeakA 最大峰值电流	@70°C		Amps					
IrmsA 实效值电流	@70°C	Amps					
Surge/Pulse voltage 冲击电压	140% rated voltage max		VDC					
E.S.R 等效串联阻抗抗值			Standard 依循标准	IEC384 -2				
Safety approval安规认证			Dimension(尺寸)mm					
			W±0.5 23.5 d±0.05 0.8	H±0.5 16.1 L.L±3.0 25.0±3.0	T±0.5 7.6 22.5			
Remark 备注:	RoHS	Confirmation area 客户承认签回区			Operating Temperature 工作温度范围 From Minus -40 °C to Plus +85°C			Design code 设计代码: MEF 335J250VAC P:22.5
		DATE 日期: 2016-07-1			3RD ANGLE PROJECTION 第三角法			Designer 设计师
SCALE ~ UNIT mm			DRAWING NO.			Approval 核准		

